

Electric E-winch 250-3000kg

Информация за продукта



Electric winch for pulling and lifting with a powerful three-phase motor. It's budget-friendly and strong in its work.

- winch suitable for lifting (with included limit switch)
- maintenance free bearings
- protection classification IP54, insulation class F
- standard overload protection as from 1000 kg
- powerful three-phase motor for multirange voltage:
230 – 400V / 50 Hz - three phase
480V / 60 Hz (torque -20%, speed +20%)
- 1 speed pendant control with 1m cable
- standard 2 meter power cable including 16A CEEplug
- 1 layer of paint

Options:

- for pulling applications (without included limit switch)
- pressure roller (PR)
- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- external limit switch (EL)
- protection classification IP55 (IP55)

Маркировка: CE - маркировка

| Продуктов номер | WLL тон | Lifting speed m/min | Мощност kW | Rope capacity m | Capacity top layer kg | Диаметър на въжето мм | A1 | A2 | A3 | A4 | A5 | A6 | A7 | A8 | B | B1 | C | C1 | C2 | D | D1 | Тегло кг |
|-----------------|------------|------------------------|---------------|--------------------|--------------------------|--------------------------|-----|-----|-----|----|-----|-----|----|----|-----|-----|-----|-----|----|-----|-----|-------------|
| E-W250 | 0,25 | 5,2 | 0,37 | 122 | 109 | 4 | 269 | 151 | 222 | 47 | 59 | 146 | 64 | 17 | 550 | 440 | 355 | 190 | 6 | 55 | 150 | 52 |
| E-W500 | 0,5 | 5,4 | 0,75 | 45 | 247 | 6 | 269 | 189 | 222 | 47 | 59 | 146 | 64 | 17 | 550 | 440 | 355 | 190 | 6 | 55 | 150 | 60 |
| E-W1000 | 1 | 3,5 | 1,1 | 100 | 570 | 8 | 475 | 172 | 405 | 70 | 130 | 265 | 80 | 27 | 610 | 500 | 455 | 255 | 8 | 102 | 220 | 107 |
| E-W1500 | 1,5 | 4,4 | 1,8 | 55 | 927 | 10 | 475 | 211 | 405 | 70 | 130 | 265 | 80 | 27 | 610 | 500 | 455 | 255 | 8 | 102 | 220 | 122 |
| E-W2000 | 2 | 4,7 | 2 | 94 | 998 | 12 | 475 | 220 | 405 | 70 | 149 | 241 | 85 | 27 | 700 | 570 | 515 | 260 | 8 | 168 | 325 | 180 |
| E-W3000 | 3 | 3,6 | 3 | 54 | 1 957 | 14 | 475 | 240 | 405 | 70 | 149 | 241 | 85 | 27 | 700 | 570 | 515 | 260 | 8 | 168 | 325 | 192 |

Чертеж

