



Heavy Duty Air Chain Hoists Red Rooster TMH (10.000, 15.000 & 20.000 kg)

Информация за продукта

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market. With M4 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a supporting eye for easy installation.

Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Маркировка: Съгласно релевантния стандарт, CE - маркировка

Стандарт: EN 14492-2

Продуктов номер	WLL тон	Модел	Верига бр.	Консумация на въздух спускане л/сек	Консумация на въздух повдигане л/сек	Скорост повдигане макс. товар м/мин	Скорост спускане макс. товар м/мин	Скорост на повдигане без товар м/мин	A	B	C	D	E	F	G	H	I	J	K	L	M	N	Тегло кг
ТМН10ТC2	10	Cord control	2	71,7	58,3	1,6	3,2	3,3	860	463	188	275	221	60	214	266	315	65	∅60	45	351	∅61	206
ТМН10ТP2E	10	Pendant control	2	71,7	58,3	1,6	3,2	3,3	860	463	188	275	221	60	214	266	315	65	∅60	45	351	∅61	206
ТМН15C3	15	Cord control	3	71,7	58,3	1,05	2,1	2,2	880	695	635	255	270	52	250	266	315	67	∅84	58	436	∅84	316
ТМН15P3E	15	Pendant control	3	71,7	58,3	1,05	2,1	2,2	880	695	635	255	270	52	250	266	315	67	∅84	58	436	∅84	316
ТМН20C4	20	Cord control	4	71,7	58,3	0,8	1,6	1,6	1 028	500	150	350	-	64	315	326	387	80	∅110	78	475	∅110	466
ТМН20P4E	20	Pendant control	4	71,7	58,3	0,8	1,6	1,6	1 028	500	150	350	-	64	315	326	387	80	∅110	78	475	∅110	466

Чертеж

