



Electric pallet truck

Product information

Easy-to-use, lightweight, durable and compact size electric pallet truck. Equipped with electric lifting and lowering functions. Due to the stepless driving motor and small turning radius (1353 mm), the pallet truck is easy to use in narrow spaces and corridors. Max travelling speed 4-5 km/h depending of load. Hill climbing ability, empty 20% and loaded 6%. 10 Ah lithium battery ensures 3 hours of continuous operating time depending on the load. Separate charger enables charging of an additional battery during the use of the electric pallet truck. Charging time of the battery is 5 hours. Carbon brushless motor ensures carefree use and fast maintenance.

Product code of extra battery (fits both models): **HAVA1500ELECAKKU**

Product code of charger (2 Ah) (fits both models): **HAVA1500ELECLATURI**

Content of the delivery:

- Electric pallet truck
- 1 pcs battery 48V / 10 Ah
- 1 pcs charger 2 Ah

Temperature range: -10°C - (+)55°C

Note: Different from the picture, there are double bogey wheels in front of the forks

| Part Code | WLL ton | Fork length mm | Width of forks mm | Minimum height of fork mm | Motor kW | Max. lifting height mm | Power of lifting motor kW | Weight kg |
|--------------|---------|----------------|-------------------|---------------------------|----------|------------------------|---------------------------|-----------|
| HAVA1500ELEC | 1.5 | 1,150 | 550 | 82 | 0,75 | 197 | 0,8 | 117 |

Technical data

SPARE PARTS


| Spare part (product code) | Description | Suitable for pallet truck (product code) |
|---------------------------|---|--|
| HAVA1500ELECAKKU | Battery 48 V, 10 Ah | HAVA1500ELEC |
| HAVA1500ELECLATURI | Charger | HAVA1500ELEC |
| HAVA1500ELECOP | Drive wheel \varnothing 140 x 55 mm | HAVA1500ELEC |

Also other spare parts available, ask our sales for more information

FRAME



HANDLE ASSY






HYDRAULIC SYSTEM



CYLINDER



DRIVE SYSTEM



DRIVE UNIT



FORK-LOADING WHEEL

