



## Push trolley

### Product information

Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -10°C - (+)50°C

**Finish:** Painted, yellow

**Standard:** EN 13157

**Safety factor:** 4:1

Part Code	WLL ton	Beam width mm	Min. Radius Curve m	B mm	J mm	K mm	F mm	E mm	D mm	L mm	H mm	G mm	Weight kg
SIVA05H	0.5	55-220	0.5	285	198	158	12.5	40	3	55	80	25	5
SIVA05HL	0.5	55-305	0.5	385	198	158	12.5	40	3	55	80	25	5.4
SIVA10H	1	58-220	0.7	300	238	183	17	31	3	68	96	29	8.8
SIVA10HL	1	58-305	0.7	238	-	183	17	31	3	68	96	29	9.3
SIVA20H	2	66-220	0.9	300	277	208	20	31	3	80	110	36	14
SIVA20HL	2	66-305	0.9	405	277	208	20	31	3	80	110	36	14.8
SIVA30H	3	74-220	1.2	328	324	249	26	31	3	100	132	46	23
SIVA30HL	3	74-305	1.2	429	324	249	26	31	~3	100	132	46	24.1
SIVA50H	5	90-220	1	354	373	296.5	28	40	5	120	155	52	40
SIVA50HL	5	90-305	1	435	373	296.5	28	40	~5	120	155	52	41.1

# Blueprint

