



Eye Foundry Hook X-047

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Designed for the assembly of chain slings where wide throat openings are necessary

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Standard: EN 1677-1

Warning: Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	A mm	D mm	H mm	K mm	P mm	T mm	Weight kg
VAL1006	6	1.4	18	6	22	93	48	17	0.33
VAL1078	7-8	2.5	24	12	30	123	62	19	0.8
VAL1010	10	4	32	15	35	149	74	23	1.6
VAL1013	13	6.7	40	19	39	180	88	32	2.6
VAL1016	16	10	50	25	46	213	98	41	4.5
VAL1020	20	16	60	26	59	248	113	58	9.3

Blueprint

