



## Chain sling 2-legs with latch hooks and grab hooks, grade 80

### Product information

2-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

| <b>Part Code</b> | <b>Chain diameter<br/>mm</b> | <b>Basket Hitch 0-45°<br/>ton</b> | <b>Basket Hitch 45°-60°<br/>ton</b> |
|------------------|------------------------------|-----------------------------------|-------------------------------------|
| NKS06201L        | 6                            | 1.6                               | 1.12                                |
| NKS07201L        | 7                            | 2.12                              | 1.5                                 |
| NKS08201L        | 8                            | 2.8                               | 2                                   |
| NKS10201L        | 10                           | 4.25                              | 3.15                                |
| NKS13201L        | 13                           | 7.5                               | 5.3                                 |
| NKS16201L        | 16                           | 11.2                              | 8                                   |
| NKS20201L        | 20                           | 17                                | 12.5                                |
| NKS22201L        | 22                           | 21.2                              | 15                                  |
| NKS26201L        | 26                           | 30                                | 21.2                                |
| NKS32201L        | 32                           | 45                                | 31.5                                |

## Blueprint

