



## Chain sling 3-legs with latch hooks and grab hooks, grade 80

### Product information

3-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

<b>Part Code</b>	<b>Chain size mm</b>	<b>WLL 45- 60° ton</b>	<b>WLL 0-45° ton</b>
NKS06301L	6	1.7	2.36
NKS07301L	7	2.24	3.15
NKS08301L	8	3	4.25
NKS10301L	10	4.75	6.7
NKS13301L	13	8	11.2
NKS16301L	16	11.8	17
NKS20301L	20	19	26.5
NKS22301L	22	22.4	31.5
NKS26301L	26	31.5	45
NKS32301L	32	47.5	67

## Blueprint

