



## Chain sling 3-legs with safety hooks and grab hooks, grade 80

### Product information

3-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

| <b>Part Code</b> | <b>Chain size<br/>mm</b> | <b>WLL 45- 60°<br/>ton</b> | <b>WLL 0-45°<br/>ton</b> |
|------------------|--------------------------|----------------------------|--------------------------|
| NKV06301L        | 6                        | 1.7                        | 2.36                     |
| NKV07301L        | 7                        | 2.24                       | 3.15                     |
| NKV08301L        | 8                        | 3                          | 4.25                     |
| NKV10301L        | 10                       | 4.75                       | 6.7                      |
| NKV13301L        | 13                       | 8                          | 11.2                     |
| NKV16301L        | 16                       | 11.8                       | 17                       |
| NKV20301L        | 20                       | 19                         | 26.5                     |
| NKV22301L        | 22                       | 22.4                       | 31.5                     |
| NKV26301L        | 26                       | 31.5                       | 45                       |
| NKV32301L        | 32                       | 47.5                       | 67                       |

## Blueprint

