



Clevis sling hook with latch , grade 100

Product information

Hook is equipped with spring loaded safety latch. Attachment directly to the chain with clevis link.

Material: Steel

Marking: CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, blue

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

| Part Code | WLL ton | For chain dia. mm | P1 mm | H mm | K mm | Weight kg |
|------------|------------|----------------------|----------|---------|---------|--------------|
| SALKAH1006 | 1.4 | 6 | 18 | 21 | 75 | 0.33 |
| SALKAH1078 | 2.5 | 8 | 25 | 27 | 85 | 0.7 |
| SALKAH1010 | 4 | 10 | 28 | 33 | 104 | 1.3 |
| SALKAH1013 | 6.7 | 13 | 38 | 42 | 128 | 2.3 |
| SALKAH1016 | 10 | 16 | 44 | 50 | 150 | 3.6 |
| SALKAH1020 | 16 | 20 | 52 | 56 | 180 | 7.3 |
| SALKAH1022 | 19 | 22 | 66 | 62 | 213 | 12.1 |

Technical data

SPARE PARTS

| Spare part set (product code) Inc. latch, spring and pin/nut | Fits the hook (product code) |
|--|------------------------------|
| SALKAHVO1006S | SALKAH1006 |
| SALKAHVO1078S | SALKAH1078 |
| SALKAHVO1010S | SALKAH1010 |
| SALKAHVO1013S | SALKAH1013 |
| SALKAHVO1016S | SALKAH1016 |
| SALKAHVO1020S | SALKAH1020 |
| SALKAHVO1022S | SALKAH1022 |

Blueprint

