



Clevis sling hook with latch, grade 80

Product information

Clevis sling hook with latch, grade 80.

Hook is equipped with spring loaded safety latch. Attachment directly to the chain with clevis link.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-2

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part Code	WLL ton	EWL mm	For chain dia. mm	K mm	H mm	E mm	M mm	R mm	B mm	Weight kg
SALKH6	1.12	76	6	76	23	26	8	35	32	0.32
SALKH78	2	85	7/8	85	32	29	9.5	37	37	0.48
SALKH10	3.15	104	10	104	35	32	13	46	49	0.95
SALKH13	5.3	128	13	128	42	36	16	56	56	1.8
SALKH16	8	150	16	150	54	55	21	60	70	3.4
SALKH20	12.5	180	20	180	58	61	24	79	77	6

Technical data

SPARE PARTS

Spare part set (product code) | Inc. latch, spring and pin/nut

Fits the hook (product code)

SALKHVO6S

SALKH6

SALKHVO78S

SALKH78

SALKHVO10S

SALKH10

SALKHVO13S

SALKH13

SALKHVO16S

SALKH16

SALKHVO20S

SALKH20

Blueprint

