



Eye grab hook, grade 80

Product information

Eye grab hook is used for shortening chain legs of a sling. The grab hook is attached to the master link with the same connection link as the chain.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-1

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

| Part Code | WLL ton | For chain dia. mm | A mm | K mm | P mm | Weight kg |
|-----------|---------|-------------------|------|------|------|-----------|
| LYK6 | 1.12 | 6 | 13 | 51 | 8 | 0.14 |
| LYK78 | 2 | 7/8 | 18 | 61.5 | 10 | 0.245 |
| LYK10 | 3.15 | 10 | 20 | 80 | 13 | 0.65 |
| LYK13 | 5.3 | 13 | 26 | 99 | 16 | 1.39 |
| LYK16 | 8 | 16 | 30 | 104 | 20 | 2.2 |
| LYK20 | 12.5 | 20 | 37 | 140 | 25 | 4.6 |
| LYK22 | 15 | 22 | 44 | 165 | 28 | 8.2 |
| LYK26 | 21.2 | 26 | 41 | 188 | 30 | 9.8 |
| LYK32 | 31.5 | 32 | 57 | 228 | 38 | 19.4 |

Blueprint

