



## Master link oversized, grade 80

### Product information

Extra large masterlink for chain sling assemblies.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton	EWL mm	For chain mm, 1-leg	For chain mm, 2-leg	A mm	B mm	D mm	Weight kg
NOR16B7	3.2	190	10	7/8	190	100	16	0.86
NORY025	6.4	300	13	10	300	210	25	5.53
NOR22B7	7	210	13	10	210	110	22	1.83
NORY032	11	300	16	13	300	210	32	5.94
NOR28B7	11.5	270	16	13/16	270	140	28	3.8
NOR32B6	17	270	22	20	270	140	32	5.05
NOR38B7	19	400	22	20	420	220	38	10.78
NOR38B6	25.1	420	26	22	270	140	38	7.29
NOR45B7	27	470	26	22	470	250	45	17.06
NOR50B6	45	380	36	32	380	200	50	17.65
NOR60B6	65	430	36	32	430	220	60	28.85

## Blueprint

