



Shortening clutch sling hook, grade 80

Product information

Hook is equipped with spring loaded safety latch.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-2

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

| Part Code | WLL ton | For chain Ø mm | A mm | B mm | C mm | E mm | M mm | N mm | L mm | Ø mm | Weight kg |
|-----------|---------|----------------|------|------|------|------|-------|------|------|------|-----------|
| SALKH6TK | 1.12 | 6 | 8 | 40 | 29 | 20 | 66 | 11 | 136 | 17 | 0.5 |
| SALKH78TK | 2 | 7/8 | 10 | 45 | 33 | 27 | 84 | 13 | 172 | 27 | 0.9 |
| SALKH10TK | 3.15 | 10 | 12 | 56 | 42 | 33 | 103 | 11 | 215 | 34 | 1.7 |
| SALKH13TK | 5.3 | 13 | 15 | 75 | 57 | 40 | 133 | 20 | 258 | 45 | 3.4 |
| SALKH16TK | 8 | 16 | 18.5 | 82 | 72 | 44 | 156.7 | 26.5 | 305 | 56 | 5.57 |

Blueprint

