



Horizontal Lifting Clamp FHX/FHSX

Product information

For horizontal lifting and transporting of steel plates and other non-deflecting materials. FHX/FHSX lifting clamps only to be used and sold in pairs (or multiple pairs).

Model FHX: Standard clamp

Model FHSX: Clamp with enlarged jaw opening.

- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

Temperature range: - 40°C up to +100°C.

Standard: EN 13155

Note: Must always be used in pairs (or multiple pairs)

Warning: Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm²)

Part Code	Code	WLL ton	Jaw width mm	V mm	S mm	W mm	T mm	H mm	X mm	U mm	Y mm	Weight kg
LTFHX1	1 FHX	1	0-35	140	99	10	25	11.5	65	188	15	2.6
LTFHX2	2 FHX	2	0-60	180	118	15	30.5	19.5	90	287	16	7
LTFHSX2	2 FHSX	2	0-100	180	120	15	30.5	19.5	90	383	15	9.2
LTFHX4	4 FHX	4	0-60	220	145	25	30.5	19.5	105	304	20	13
LTFHSX4	4 FHSX	4	0-100	220	145	25	30.5	19.5	105	414	20	15
LTFHX6	6 FHX	6	0-60	220	145	25	30.5	19.5	110	307	20	14
LTFHSX6	6 FHSX	6	0-100	220	145	25	30.5	19.5	120	414	20	16.5
LTFHSX8	8 FHSX	8	0-100	225	135	35	30.5	19.5	120	428	30	21
LTFHSX100	10 FHSX	10	0-100	225	135	35	30.5	19.5	120	428	30	22

Blueprint

