



Pipe Lifting Clamp TPH

Product information

General: Horizontal pipe lifting clamp TPH/TPH-HD - Non marking. Clamp for horizontal lifting and transporting of steel and concrete pipes without damaging the product.

Model THP: Standard clamp

Model THP-HD: special for extreme heavy duty lifting situations

Features:

- TPH Jaw is covered with a special high quality pressure resistant plastic.
- TPH-HD Jaw is covered with special high quality extreme high pressure resistant plastic.
- Maintenance-friendly clamps, plastic pressure resistant cover is easy to change.
- TPH-HD has special handle for easy handling.
- Compact design and high lifting capacity.
- Lightweight design for easy handling.
- Tough quality heavy duty body.

Marking: According to standard, Type, serial number, WLL, Jaw opening and CE marking.

Temperature range: TPH: - 40°C to + 50°C. / TPH-HD - 30°C to + 80°C.

Standard: EN 13155

| Part Code | Code | WLL ton | Jaw width mm | V mm | S mm | W mm | U mm | T mm | X mm | Y mm | Weight kg |
|-----------|---------|---------|--------------|------|------|------|------|------|------|------|-----------|
| PTTPH151 | 1.5 TPH | 1.5 | 40 | 120 | 70 | 50 | 185 | 16 | 41 | 25 | 2 |
| PTTPH30 | 3 TPH | 3 | 40 | 120 | 70 | 50 | 185 | 16 | 41 | 25 | 2 |
| PTTPH40 | 4 TPH | 4 | 50 | 140 | 70 | 58 | 204 | 26 | 41 | 25 | 3 |
| PTTPH60 | 6 TPH | 6 | 50 | 140 | 70 | 58 | 204 | 26 | 41 | 25 | 3 |
| PTTPH80 | 8 TPH | 8 | 70 | 140 | 70 | 58 | 224 | 26 | 45 | 25 | 3.4 |
| PTTPH100 | 10TPH | 10 | 70 | 140 | 70 | 58 | 224 | 26 | 85 | 45 | 5 |

Blueprint

