



Coated webbing slings 2 - 4 t

Product information

Double layered Duplex lifting slings, which are covered with special plastic. Extreme cut and abrasion resistance. These slings can be used to lift sharp-edged items without special corner protectors. Folded reinforced eyes as standard. Also available with one-sided and partial plastic coating.

Features: RFID-ready

Material: 100% polyester

Marking: According to standard, CE-marked

Temperature range: -40°C - +100 °C

Standard: EN 1492-1

Note: Color coded

Warning: Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range! Also available with higher WLL.

Safety factor: 7:1

Part Code	WLL ton	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	EWL m	Webbing width mm	Colour
SNVS202	2	1.6	4	2.8	2	2	80	Green
SNVS203	2	1.6	4	2.8	2	3	80	Green
SNVS204	2	1.6	4	2.8	2	4	80	Green
SNVS205	2	1.6	4	2.8	2	5	80	Green
SNVS206	2	1.6	4	2.8	2	6	80	Green
SNVS208	2	1.6	4	2.8	2	8	80	Green

SNVS210	2	1.6	4	2.8	2	10	80	Green
SNVS212	2	1.6	4	2.8	2	12	80	Green
SNVS214	2	1.6	4	2.8	2	14	80	Green
SNVS302	3	2.4	6	4.2	3	2	100	yellow
SNVS303	3	2.4	6	4.2	3	3	100	yellow
SNVS304	3	2.4	6	4.2	3	4	100	yellow
SNVS305	3	2.4	6	4.2	3	5	100	yellow
SNVS306	3	2.4	6	4.2	3	6	100	yellow
SNVS308	3	2.4	6	4.2	3	8	100	yellow
SNVS310	3	2.4	6	4.2	3	10	100	yellow
SNVS312	3	2.4	6	4.2	3	12	100	yellow
SNVS314	3	2.4	6	4.2	3	14	100	yellow
SNVS402	4	3.2	8	5.6	4	2	130	Grey
SNVS403	4	3.2	8	5.6	4	3	130	Grey
SNVS404	4	3.2	8	5.6	4	4	130	Grey
SNVS405	4	3.2	8	5.6	4	5	130	Grey
SNVS406	4	3.2	8	5.6	4	6	130	Grey
SNVS408	4	3.2	8	5.6	4	8	130	Grey
SNVS410	4	3.2	8	5.6	4	10	130	Grey
SNVS412	4	3.2	8	5.6	4	12	130	Grey
SNVS414	4	3.2	8	5.6	4	14	130	Grey