

## Swivel Eye Bolt Codipro SEB UP

### Product information



The SEB lifting ring is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

#### Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load
- Safe alternative to C15 DIN 580 eye bolts.
- Torque key adaptor available on request.

**Material:** High tensile steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +200°C

**Standard:** EN 1677-1

*except grade/WLL*

**Note:** On request the product can be certified for lashing.

**Safety factor:** 5:1

Part Code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	L1 mm	S mm	X mm	Weight kg
NS8R08SEB	0.4	M 8 (x1.25)	6	30	34	60	57	14	6	20	0.24
NS8R10SEB	0.5	M 10 (x1.50)	10	30	34	60	57	17	6	20	0.24
NS8R12SEB	0.8	M 12 (x1.75)	15	30	34	60	57	21	6	20	0.24
NS8R16SEB	1.4	M 16 (x2)	50	38	45	88	80	27	8	35	0.8
NS8R20SEB	2	M 20 (x2.5)	100	38	45	88	80	30	8	35	0.8
NS8R24SEB	3.2	M 24 (x3)	160	38	45	88	80	36	14	35	0.8
NS8R30SEB	5.5	M 30 (x3.5)	250	58	70	115	106	45	14	50	2.7
NS8R36SEB	9	M 36 (x4)	320	83	94	168	155	54	14	70	7

## Blueprint

