

Weld-On Load Ring 8-082



Product information

- Pivots 180°, designed minimizes head room.
- Load rated parts are 100% magnaflux crack detected.
- The two points of attachment facilitate an even and optimal force distribution into the work piece and thus, usage of thinner base plates is possible.
- The welding block is forged out of material with excellent welding properties.
- Low profile design with high strength.
- The ring is stowable thus avoiding the hazards of tripping and snagging.

Material: Forged alloy steel, quenched and tempered.

Marking: According to standard, CE-marked

Finish: Painted.

Standard: EN 1677-1

Safety factor: 4:1

| Part Code | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | L mm | M mm | HV mm | a mm | Weight kg |
|-----------|------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|---------|--------------|
| NS8J04Y | 4 | 66 | 14 | 30 | 48 | 65 | 70 | 135 | 76 | 5 | 3 | 0.6 |
| NS8J06Y | 6.7 | 85 | 20 | 39 | 60 | 89 | 91 | 171 | 98 | 5 | 3 | 1.5 |
| NS8J10Y | 10 | 95 | 21 | 46 | 65 | 100 | 100 | 196 | 106 | 7 | 4 | 2.4 |
| NS8J16Y | 16 | 127 | 30 | 57 | 90 | 130 | 136 | 263 | 149 | 8 | 4 | 5.5 |
| NS8J30Y | 31.5 | 178 | 42 | 75 | 130 | 160 | 195 | 375 | 213 | 15 | 4 | 15.8 |

Blueprint

