



Double Swivel Shackle Codipro DSS UP

Product information

The universal swivel shackle DSS is a double swivel ring. It is specially designed for simultaneously lifting and rotating heavy loads. Its double swivel action ensures perfect alignment with the sling.

Features:

- Swiveling under load
- Usable for any kind of lifting operation
- The tightening torque is stamped on all lifting rings in the GRADUP range.

Material: High tensile steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +200°C

Standard: EN 1677-1

except grade/WLL

Note: On request the product can be certified for lashing.

Safety factor: 5:1

Part Code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L1 mm	S mm	Weight kg
NS8KL24DSS	4.5	M 24 (x3)	160	61	31	70	98	73	149	33	36	19	5.4
NS8KL30DSS	7.7	M 30 (x3.5)	250	61	31	70	98	73	149	33	45	19	5.5
NS8KL33DSS	8.5	M 33 (x3.5)	250	61	31	70	98	73	149	33	50	19	5.5
NS8KL36DSS	11	M 36 (x4)	320	61	31	70	98	73	149	33	54	19	5.5
NS8KL39DSS	12	M 39 (x4)	320	61	31	70	98	73	149	33	58	19	5.7
NS8KL42DSS	13	M 42 (x4,5)	400	61	31	70	98	73	149	33	63	19	5.8
NS8KL45DSS	14.5	M 45 (x4,5)	400	61	31	70	98	73	149	33	63	19	5.9
NS8KL48DSS	17	M 48 (x5)	600	79	38	90	123	91	182	45	68	19	11
NS8KL52DSS	19	M 52 (x5)	600	79	38	90	123	91	182	45	68	19	12.2
NS8KL56DSS	22	M 56 (x5,5)	600	79	38	90	123	91	182	45	78	19	11.3
NS8KL64DSS	25	M 64 (x6)	600	79	38	95	123	91	182	45	90	19	12.2

Blueprint

