

Weld-on lifting point, grade 80



Product information

Weld-on lifting point for all lifting directions. Equipped with a spring that holds the eye in desired position.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C - (+)200°C

Finish: Painted, yellow

Standard: EN 1677-1

Safety factor: 4:1

Grade: 8

Part Code	WLL ton	A mm	B mm	D mm	M mm	Weight kg
NS8HI1	1.12	41	78.5	13	37	0.4
NS8HI2	2	42	88	14	40	0.47
NS8HI3	3.15	45	94	17	42.5	0.69
NS8HI5	5.3	55	118	22	50	1.46
NS8HI8	8	70	141	26.5	66.5	2.5
NS8HI15	15	97	188	34	90	5.79
NS8HI20	20	149	240	46	125	15.37

Technical data

WORKING LOAD LIMITS

Product	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
NS8HI1	1,12	1,12	2,24	2,24	1,57	1,12	2,35	1,68
NS8HI2	2	2	4	4	2,8	2	4,2	3
NS8HI3	3,15							

Blueprint

