



## Stainless steel shackles, approved for lifting

### Product information

Stainless steel shackles approved for lifting.

**Material:** AISI 316

**Marking:** CE-marked

**Warning:** Not to be heat-treated

**Safety factor:** 5:1

| Part code | WLL<br>ton | a<br>mm | b<br>mm | c<br>mm | d<br>mm | e<br>mm | f<br>mm | Weight<br>kg | Delivery time<br>days |
|-----------|------------|---------|---------|---------|---------|---------|---------|--------------|-----------------------|
| SAKDH0400 | 0.4        | 8       | 8       | 16      | 16      | 32      | 52      | 0.06         | 14                    |
| SAKDH0600 | 0.6        | 10      | 10      | 19      | 20      | 40      | 64      | 0.12         | 14                    |
| SAKDH0900 | 0.9        | 12      | 12      | 24      | 25      | 48      | 78      | 0.21         | 14                    |
| SAKDH1500 | 1.5        | 13      | 16      | 31      | 24      | 52      | 90      | 0.34         | 14                    |
| SAKDH2500 | 2.5        | 16      | 20      | 38      | 28      | 64      | 110     | 0.61         | 14                    |
| SAKDH3000 | 3          | 19      | 22      | 44      | 32      | 72      | 124     | 0.9          | 14                    |
| SAKDH4000 | 4          | 22      | 25      | 50      | 37      | 74      | 134     | 1.08         | 14                    |
| SAKDH6000 | 6          | 25      | 30      | 57      | 40      | 94      | 162     | 2.25         | 14                    |

Blueprint

