

## Steel Wire Rope 6x36WS-FC

### Product information



ISO 4309 Rope Category No: RCN.09

**Rope construction:** 6x36WS-FC

**Marking:** According to standard

**Standard:** EN 12385-4


**Fill factor:** 0.5

**RCN:** 09

Slings



Overhead cranes



Part Code	Rope Diameter,	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay.	Min. Breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
TEK21608	8	1,770	Galvanized	sZ	37.4	25.2	A-1	24
TEK21610	10	1,770	Galvanized	sZ	58.4	39.3	A-1	37
TEK21612	12	1,770	Galvanized	sZ	84.1	56.6	A-1	53
TEK21614	14	1,770	Galvanized	sZ	114	77	A-1	72
TEK21616	16	1,770	Galvanized	sZ	150	101	A-1	94
TEK21618	18	1,770	Galvanized	sZ	189	127	A-1	119
TEK21620	20	1,770	Galvanized	sZ	234	157	A-1	147
TEK21622	22	1,770	Galvanized	sZ	283	190	A-1	178
TEK21624	24	1,770	Galvanized	sZ	336	226	A-1	211
TEK21626	26	1,770	Galvanized	sZ	395	266	A-1	248
TEK21628	28	1,770	Galvanized	sZ	458	308	A-1	288
TEK21630	30	1,770	Galvanized	sZ	526	354	A-1	330
TEK21632	32	1,770	Galvanized	sZ	598	402	A-1	376