

Steel Wire Rope 6x36WS-IWRC

Product information



ISO 4309 Rope Category No: All Diameters RCN.09

Rope construction: 6x36WS-IWRC.

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.59

RCN: 09

Slings




Winch rope



Stay rope



Overhead cranes



Tower crane



Container crane



Mobile port crane



Offshore crane



Loading crane



Crawler crane



Piling crane



Ladle crane




STS crane



Straddle carrier



RTG



Part Code	Rope Diameter,	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force, kN	Steel area mm ²	Lubrication	Weight kg/100m
TEK26508	8	1,770	Galvanized	sZ	40.3	29.4	A-1	26.2
TEK26510	10	1,770	Galvanized	sZ	63	46	A-1	40.9
TEK26512	12	1,770	Galvanized	sZ	90.7	66.2	A-1	58.9
TEK26513	13	1,770	Galvanized	sZ	106	77.7	A-1	69.1
TEK26514	14	1,770	Galvanized	sZ	124	90.2	A-1	80.2
TEK26516	16	1,770	Galvanized	sZ	161	118	A-1	105
TEK26518	18	1,770	Galvanized	sZ	204	149	A-1	133
TEK26520	20	1,770	Galvanized	sZ	252	184	A-1	164
TEK26522	22	1,770	Galvanized	sZ	305	223	A-1	198
TEK26526	26	1,770	Galvanized	sZ	426	311	A-1	276
TEK26528	28	1,770	Galvanized	sZ	494	361	A-1	321
TEK26530	30	1,770	Galvanized	sZ	567	414	A-1	368
TEK26532	32	1,770	Galvanized	sZ	645	471	A-1	419