



## Steel Wire Rope 35x7 (Rotation resistant)

### Product information



**Typical applications:** Hoist rope for tower cranes, mobile cranes, electrical hoists and other applications where rotation resistant rope is required.

**ISO 4309 Rope Category No:** All Diameters **RCN.23-2**

**Rope construction:** Rotation resistant, made out of conventional strands.

**Marking:** According to standard

**Standard:** EN 12385-4

**Fill factor:** 0.61

**RCN:** 23-2

Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay.	Min. Breaking force, kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
ANKO08	8	2,160	Galvanized	sZ	48.4	30.7	A-1	29
ANKO10	10	2,160	Galvanized	sZ	75.6	48	A-1	45
ANKO12	12	2,160	Galvanized	sZ	109	69.1	A-1	65
ANKO14	14	2,160	Galvanized	sZ	148	94.1	A-1	89
ANKO16	16	2,160	Galvanized	sZ	194	123	A-1	116
ANKO18	18	2,160	Galvanized	sZ	245	156	A-1	147
ANKO19	19	2,160	Galvanized	sZ	273	173	A-1	164
ANKO20	20	2,160	Galvanized	sZ	302	192	A-1	182
ANKO22	22	2,160	Galvanized	sZ	366	232	A-1	220