



## Steel Wire Rope 35x7 (Rotation resistant)

### Product information



**Typical applications:** Hoist rope for tower cranes, mobile cranes, electrical hoists and other applications where rotation resistant rope is required.

**ISO 4309 Rope Category No:** All Diameters **RCN.23-2**

**Rope construction:** Rotation resistant, made out of conventional strands.

**Marking:** According to standard

**Standard:** EN 12385-4

**Fill factor:** 0.61

**RCN:** 23-2

Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Steel area mm <sup>2</sup>	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
ANKO08	8	2,160	-	-	Galvanized	-	-
ANKO10	10	2,160	-	-	Galvanized	-	-
ANKO12	12	2,160	-	-	Galvanized	-	-
ANKO14	14	2,160	-	-	Galvanized	-	-
ANKO16	16	2,160	-	-	Galvanized	-	-
ANKO18	18	2,160	-	-	Galvanized	-	-
ANKO19	19	2,160	-	-	Galvanized	-	-
ANKO20	20	2,160	-	-	Galvanized	-	-
ANKO22	22	2,160	-	-	Galvanized	-	-