

Wedge Socket for Lifts

Product information

Symmetrical Wedge Socket for stranded steel wire ropes according to EN 12385-5 for lifts.

Marking: According to standard

Temperature range: -20°C up to +100°C

Finish: Galvanized

Standard: EN 13411-7

DIN 15315 replaced by EN 13411-7

Warning: Tensile strength should not exceed 1770 N/mm²



| Part Code | Rope Ø range mm | Finish | B1 mm | B2 mm | B3 mm | C mm | D mm | E mm | H1 mm | H2 mm | H3 mm | R mm | S mm | Weight kg |
|-----------|-----------------|------------|-------|-------|-------|------|------|------|-------|-------|-------|------|------|-----------|
| KII08 | 6-8 | Galvanized | 12 | 14 | 11 | 37 | 12 | 20 | 150 | 75 | 92 | 12,5 | 4 | 0.57 |
| KII11 | 9-11 | Galvanized | 15 | 17 | 14 | 48 | 16 | 26 | 190 | 95 | 117 | 16 | 6 | 1.05 |
| KII14 | 12-14 | Galvanized | 20 | 22 | 18 | 58 | 18 | 32 | 230 | 115 | 141 | 19 | 8 | 1.89 |
| KII17 | 15-17 | Galvanized | 23 | 25 | 21 | 70 | 22 | 36 | 260 | 130 | 162 | 23 | 10 | 3.26 |
| KII20 | 18-20 | Galvanized | 26 | 27 | 24 | 82 | 25 | 40 | 300 | 150 | 186 | 26 | 12 | 5.25 |

Blueprint

