

## Female Swivel eye bolt Codipro FE SEB UP

### Product information



The SEB lifting eye nut is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

#### Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load.
- Safe alternative to C15 DIN 580 eye nuts.
- Torque key adaptor available on request.

**Material:** High tensile steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +200°C

**Standard:** EN 1677-1

*except grade/WLL*

**Safety factor:** 5:1

Part Code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	L max. mm	Weight kg
NS8M08FE.SEB	0.4	M 8 (x1,25)	6	38	45	88	80	22	0.8
NS8M10FE.SEB	0.5	M 10 (x1,50)	10	38	45	88	80	22	0.8
NS8M12FE.SEB	0.8	M 12 (x1,75)	15	38	45	88	80	22	0.8
NS8M16FE.SEB	1.4	M 16 (x2)	50	38	45	88	80	22	0.8
NS8M20FE.SEB	2	M 20 (x2,5)	100	55	70	115	106	35	2.5
NS8M24FE.SEB	3.4	M 24 (x3)	160	77	94	168	155	48	6.3
NS8M30FE.SEB	5.5	M 30 (x3,5)	250	77	94	168	155	48	6.3
NS8M36FE.SEB	9	M 36 (x4)	320	77	94	168	155	48	6.3

## Blueprint

