



Geared trolleys with washer adjustment

Product information

- the trolley moves on the beam by pulling the hand chain
- standard length of a hand chain is approx. 2,5 m, allowing for mounting the trolley at about 3,5-4 m height
- 0,5 / 1,0 / 2,0 t models can be integrated with Haklift KTHA and VTHA hoists
- also available with longer chain
- suitable for I- and T-beams
- Equipped with rubber end stops
- the hoist/lifter is attached directly to the trolley eye from a hook or with a shackle
- wheels are equipped with duration lubricated ball bearings
- Each trolley has tested with 1.5x load

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -10°C - (+)50°C

Finish: Painted, orange

Standard: EN 13157

Safety factor: 4:1

Part Code	WLL ton	Beam width mm	Minimum radius mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	S mm	Weight kg
SIVA05KS	0.5	50-135	800	205	198	150	55	30	1,5-2,0	28	8	111	28	239	27	8
SIVA05KSL	0.5	130-215	800	205	278	150	55	30	1,5-2,0	28	8	111	28	239	27	8
SIVA05KSXL	0.5	215-300	800	205	363	150	55	30	1,5-2,0	28	8	111	28	239	27	8
SIVA10KS	1	55-140	1,000	242	211	174	68	30	1,5-2,0	32	10	118	32	254	28	12.4
SIVA10KSL	1	140-215	1,000	242	286	174	68	30	1,5-2,0	32	10	118	32	254	28	12.4
SIVA10KSXL	1	215-300	1,000	242	371	174	68	30	1,5-2,0	32	10	118	32	254	28	12.4
SIVA20KS	2	65-155	1,100	270	238	194	80	49	1,5-2,0	40	12	147	36	277	27	18.1
SIVA20KSL	2	150-230	1,100	270	313	194	80	49	1,5-2,0	40	12	147	36	277	27	18.1
SIVA20KSXL	2	230-300	1,100	270	383	194	80	49	1,5-2,0	40	12	147	36	277	27	18.1
SIVA30KS	3	90-160	1,300	325	246	234	100	60	2,0-3,0	49	14	177	44	287	29	30.3
SIVA30KSL	3	160-230	1,300	325	316	234	100	60	2,0-3,0	49	14	177	44	287	29	30.3
SIVA30KSXL	3	230-300	1,300	325	386	234	100	60	2,0-3,0	49	14	177	44	287	29	30.3
SIVA50KS	5	90-180	1,500	370	280	267	110	79	2,0-3,0	59	16	219	55	320	29	46.5
SIVA50KSL	5	180-230	1,500	370	330	267	110	79	2,0-3,0	59	16	219	55	320	29	46.5

Blueprint

