



Steel wire rope sling - type 1

Product information

- The steel wire rope is equipped with pressing buckles, master ring and a latch hook
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

Features: Steel core

Rope construction: 6X36-IWRC

Marking: CE-marked

Finish: Rope, hot dip galvanized | Components, painted yellow

Part Code	WLL
TER10601	0.35
TER10801	0.7
TER11001	1.05
TER11201	1.55
TER11401	2.12
TER11601	2.7
TER11801	3.4
TER12002	4.35
TER12202	5.2
TER12402	6.3
TER12602	7.2
TER12802	8.4
TER13002	9.7
TER13202	11
TER13603	14
TER14003	17
TER14403	21
TER14803	25
TER15203	29
TER15603	33.5
TER16003	39

Technical data

Working load limits (WLL)

Rope	WLL tons		
Ø	<input type="text"/>	<input type="text"/>	<input type="text"/>
mm	Straight lift	Choke hitch	Basket hitch
6	0,35	0,28	0,7
8	0,7	0,55	1,4
10	1,05	0,85	2,1
12	1,55	1,2	3,1
14	2,12	1,7	4,2
16	2,7	2,2	5,4
18	3,4	2,7	6,8
20	4,35	3,4	8,7
22	5,2	4,1	10,4
24	6,3	5	12,6
26	7,2	5,8	14,4
28	8,4	6,7	16,8
32	11	8,8	22
36	14	11,2	28
40	17	13,6	34
44	21	16,8	42

48	25	20	50
52	29	23,2	58
56	33,5	26,8	67
60	39	31,2	78

Blueprint

