



## Steel wire rope sling - type 6

### Product information

- The steel wire rope is equipped with pressing buckles and loop ends
- wire rope strength 1770 N / mm<sup>2</sup>
- also available with spliced connections, larger workloads and special ends, ask more about our sales

**Note!** The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

**Features:** Steel core

**Rope construction:** 6X36-IWRC

**Marking:** CE-marked

**Finish:** hot dip galvanized

<b>Part Code</b>	<b>WLL</b>
TER60601	0.35
TER60801	0.7
TER61001	1.05
TER61201	1.55
TER61401	2.12
TER61601	2.7
TER61801	3.4
TER62002	4.35
TER62202	5.2
TER62402	6.3
TER62602	7.2
TER62802	8.4
TER63002	9.7
TER63202	11
TER63603	14
TER64003	17
TER64403	21
TER64803	25
TER65203	29
TER65603	33.5
TER66003	39

## Technical data

### Working load limits (WLL)

Rope	WLL tons		
∅	<input type="text"/>	<input type="text"/>	<input type="text"/>
mm	Straight lift	Choke hitch	Basket hitch
6	0,35	0,28	0,7
8	0,7	0,55	1,4
10	1,05	0,85	2,1
12	1,55	1,2	3,1
14	2,12	1,7	4,2
16	2,7	2,2	5,4
18	3,4	2,7	6,8
20	4,35	3,4	8,7
22	5,2	4,1	10,4
24	6,3	5	12,6
26	7,2	5,8	14,4
28	8,4	6,7	16,8
32	11	8,8	22
36	14	11,2	28
40	17	13,6	34
44	21	16,8	42

48	25	20	50
52	29	23,2	58
56	33,5	26,8	67
60	39	31,2	78

**Blueprint**

