



Steel wire rope sling - type 7

Product information

- The steel wire rope is equipped with pressing buckles and loop/thimble ends
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

Features: Steel core

Rope construction: 6X36-IWRC

Marking: CE-marked

Finish: hot dip galvanized

Part Code	WLL
TER70601	0.35
TER70801	0.7
TER71001	1.05
TER71201	1.55
TER71401	2.12
TER71601	2.7
TER71801	3.4
TER72002	4.35
TER72202	5.2
TER72402	6.3
TER72602	7.2
TER72802	8.4
TER73002	9.7
TER73202	11
TER73603	14
TER74003	17
TER74403	21
TER74803	25
TER75203	29
TER75603	33.5
TER76003	39

Technical data

Working load limits (WLL)

Rope	WLL tons		
∅	<input type="text"/>	<input type="text"/>	<input type="text"/>
mm	Straight lift	Choke hitch	Basket hitch
6	0,35	0,28	0,7
8	0,7	0,55	1,4
10	1,05	0,85	2,1
12	1,55	1,2	3,1
14	2,12	1,7	4,2
16	2,7	2,2	5,4
18	3,4	2,7	6,8
20	4,35	3,4	8,7
22	5,2	4,1	10,4
24	6,3	5	12,6
26	7,2	5,8	14,4
28	8,4	6,7	16,8
32	11	8,8	22
36	14	11,2	28
40	17	13,6	34
44	21	16,8	42

48	25	20	50
52	29	23,2	58
56	33,5	26,8	67
60	39	31,2	78

Blueprint

