



Steel wire rope - type 8

Product information

- The steel wire rope is equipped with pressing buckles, loop end and a latch hook
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

Features: Steel core

Rope construction: 6X36-IWRC

Marking: CE-marked

Finish: Rope, hot dip galvanized | Components, painted yellow

| Part Code | WLL |
|------------------|------------|
| TER80601 | 0.35 |
| TER80801 | 0.7 |
| TER81001 | 1.05 |
| TER81201 | 1.55 |
| TER81401 | 2.12 |
| TER81601 | 2.7 |
| TER81801 | 3.4 |
| TER82002 | 4.35 |
| TER82202 | 5.2 |
| TER82402 | 6.3 |
| TER82602 | 7.2 |
| TER82802 | 8.4 |
| TER83002 | 9.7 |
| TER83202 | 11 |
| TER83603 | 14 |
| TER84003 | 17 |
| TER84403 | 21 |
| TER84803 | 25 |
| TER85203 | 29 |
| TER85603 | 33.5 |
| TER86003 | 39 |

Technical data

Working load limits (WLL)

| Rope | WLL tons | | |
|------|----------------------|----------------------|----------------------|
| ∅ | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| mm | Straight lift | Choke hitch | Basket hitch |
| 6 | 0,35 | 0,28 | 0,7 |
| 8 | 0,7 | 0,55 | 1,4 |
| 10 | 1,05 | 0,85 | 2,1 |
| 12 | 1,55 | 1,2 | 3,1 |
| 14 | 2,12 | 1,7 | 4,2 |
| 16 | 2,7 | 2,2 | 5,4 |
| 18 | 3,4 | 2,7 | 6,8 |
| 20 | 4,35 | 3,4 | 8,7 |
| 22 | 5,2 | 4,1 | 10,4 |
| 24 | 6,3 | 5 | 12,6 |
| 26 | 7,2 | 5,8 | 14,4 |
| 28 | 8,4 | 6,7 | 16,8 |
| 32 | 11 | 8,8 | 22 |
| 36 | 14 | 11,2 | 28 |
| 40 | 17 | 13,6 | 34 |
| 44 | 21 | 16,8 | 42 |

| | | | |
|----|------|------|----|
| 48 | 25 | 20 | 50 |
| 52 | 29 | 23,2 | 58 |
| 56 | 33,5 | 26,8 | 67 |
| 60 | 39 | 31,2 | 78 |

Blueprint

