



Swivel Bearing Hoist Hook X-175N

Product information

- 20,000 cycle fatigue rated to 1.5 times of 4:1 WLL
- All swivel hoist hooks are 100% magnaflux crack detected.
- Ball bearing performs fully swivel under load.

Material: Alloy steel - quenched and tempered

Marking: CE-marked, Batch number, grade, chain size

Finish: Blue painted.

Safety factor: 4:1

Grade: 10

Part Code	Code	Chain diameter mm	WLL ton	A mm	B mm	C mm	D mm	G mm	H mm	K mm	L mm	P mm	P1 mm	T mm	Weight kg
SALKAL1078KL	CC	7-8	2.5	36	29	26	13	90	27	145	184	24	20	22	1
SALKAL1010KL	DD	10	4	41	35	29	16	102	29	172	217	28	25	24	1.6
SALKAL1013KL	EE	13	6.7	46	44	38	21	122	38	218	277	35	31	31	3.3
SALKAL1016KL	FF	16	10	61	50	49	23	160	48	261	332	43	39	35	5.6
SALKAL1020KL	GG	18-20	16	74	82	62	25	196	56	327	410	61	57	47	9.5
SALKAL1022KL	HH	22	19	97	96	65	33	221	64	372	471	72	62	56	16

Blueprint

