



## Coupling Link Gunnebo, G Grabiq

### Product information

For use with master link and eye hook.

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, code and grade.

**Finish:** Painted.

**Standard:** EN 1677

**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

| <b>Part Code</b> | <b>Code</b> | <b>Chain diameter<br/>mm</b> | <b>WLL<br/>ton</b> | <b>A<br/>mm</b> | <b>B<br/>mm</b> | <b>C<br/>mm</b> | <b>F<br/>mm</b> | <b>L<br/>mm</b> | <b>Weight<br/>kg</b> |
|------------------|-------------|------------------------------|--------------------|-----------------|-----------------|-----------------|-----------------|-----------------|----------------------|
| LLA1006G         | G-6-10      | 6                            | 1.5                | 8               | 15              | 16              | 7               | 45              | 0.1                  |
| LLA1007G         | G-7-10      | 7                            | 2                  | 11              | 18              | 22              | 9               | 56              | 0.2                  |
| LLA1008G         | G-8-10      | 8                            | 2.6                | 11              | 18              | 22              | 9               | 56              | 0.2                  |
| LLA1010G         | G-10-10     | 10                           | 4                  | 13              | 25              | 26              | 12              | 68              | 0.3                  |
| LLA1013G         | G-13-10     | 13                           | 6.8                | 17              | 29              | 33              | 15              | 89              | 0.7                  |
| LLA1016G         | G-16-10     | 16                           | 10.3               | 20              | 36              | 40              | 19              | 106             | 1.4                  |
| LLA1020G         | G-20-10     | 20                           | 16                 | 26              | 43              | 44              | 23              | 125             | 2.2                  |
| LLA1022G         | G-22-10     | 22                           | 20                 | 28              | 50              | 59              | 26              | 152             | 3.6                  |
| LLA1026G         | G-26-10     | 26                           | 27.3               | 34              | 58              | 61              | 32              | 161             | 5.7                  |
| LLA1032G         | G-32-10     | 32                           | 40                 | 40              | 70              | 77              | 38              | 200             | 9.5                  |

# Blueprint

