



Open Wedge Socket G-6413

Product information

The Green Pin[®] Open Wedge Socket CP is an open wedge socket with a cotter (split) pin. The socket is made from high tensile steel, while galvanization ensures its long-term durability.

Material: high tensile steel

Marking: According to standard

Temperature range: -20°C up to +200°C

Finish: hot dipped galvanized

Standard: EN 13411-6

Part Code	Rope Ø range mm	MBL ton	Finish	Number	length a	width inside d	a mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg
KII010	7-8	8	Galvanized	0.25	128	18	128	110	51	18	16	9	36	0.79
KII015	9-10	12	Galvanized	0.5	165	20.5	165	142	62	20.5	21	11	46	1.5
KII025	11-13	20	Galvanized	1	175	25	175	146	66	25	25	12	57	2.4
KII040	14-16	25	Galvanized	2	211	31	211	176	82	31	30	15	70	4
KII050	18-19	40	Galvanized	3	252	38	252	212	95	38	35	16	80	7.4
KII070	20-22	55	Galvanized	4	288	44	288	240	110	44	41	19	95	11
KII100	24-26	75	Galvanized	5	329	51	329	274	130	51	51	22	110	16
KII120	27-29	90	Galvanized	6	375	57	375	310	144	57	57	25	130	22
KII160	30-32	110	Galvanized	7	423	63	423	350	155	63	64	28	146	31
KII180	34-36	125	Galvanized	8	474	69	474	400	163	69	64	28	148	39

Blueprint

